



O-Ring EPDM/FKM

Ausführung:

- Für Verschraubungen und Übergangverschraubungen
- Härte ca: 65° Shore
- EPDM minimale Temperatur: -40°
- FKM minimale Temperatur: -15°C

* nur für Verschraubungen PVC-U, PVC-C and ABS: 21 51 01, 21 51 11, 21 53 03, 21 53 08, 21 55 04, 21 55 13, 21 55 18, 23 51 01 und 29 51 01

d (mm)	DN (mm)	EPDM Code	Gewicht (kg)	FKM Code	Gewicht (kg)	D (mm)	D1 (mm)	D2 (mm)	closest inch (inch)
10 - 12	8	748 410 004	0.002	749 410 004	0.020	17.62	12.37	2.62	¼
16	10	748 410 005	0.002	749 410 005	0.002	20.78	15.54	2.62	¾
20	15	748 410 006	0.002	749 410 006	0.002	27.28	20.22	3.53	½
25	20	748 410 007	0.002	749 410 007	0.002	35.23	28.17	3.53	¾
32	25	748 410 008	0.003	749 410 008	0.002	39.99	32.93	3.53	1
40	32	748 410 009	0.003	749 410 009	0.007	51.33	40.65	5.34	1 ¼
50	40	748 410 010	0.004	749 410 010	0.060	57.68	46.99	5.34	1 ½
63	50	748 410 011	0.005	749 410 011	0.003	70.37	59.69	5.34	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>