



ecoFIT Verschraubung PE100 / SDR11 / d20-110mm

Ausführung:

- Konventionelle Stumpfschweissung nach DVS 2207
- IR = (IR Plus®) kompatibel
- O-Ring Dichtung EPDM/FKM
- ecoFIT Überwurfmutter Material: PP Glasfaserverstärkt
- Für die Dimensionen d75--110 bitte die Hinweise für die Montage beachten

d	DN	PN	SDR	SM	EPDM	Gewicht	FKM	Gewicht
(mm)	(mm)	(bar)			Code	(kg)	Code	(kg)
20	15	16	11	IR	753 518 606	0.048	753 528 606	0.042
25	20	16	11	IR	753 518 607	0.078	753 528 607	0.052
32	25	16	11	IR	753 518 608	0.108	753 528 608	0.083
40	32	16	11	IR	753 518 609	0.176	753 528 609	0.151
50	40	16	11	IR	753 518 610	0.241	753 528 610	0.196
63	50	16	11	IR	753 518 611	0.402	753 528 611	0.406
75	65	10	11	IR	753 518 612	0.537	753 528 612	0.520
90	80	10	11	IR	753 518 613	0.540	753 528 613	0.562
110	100	10	11	IR	753 518 614	0.783	753 528 614	0.760

d	D	G	L	L1	L2	L3	L4	e
(mm)	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	48	1	107	54.0	53	26	38	1.9
25	58	1 1/4	113	57.0	56	26	42	2.3
32	65	1 1/2	119	60.0	59	25	41	3.0
40	79	2	126	63.0	63	25	42	3.7
50	91	2 1/4	131	65.0	65	25	44	4.6
63	111	2 3/4	137	69.0	68	25	45	5.8
75	135	S107,5x3,6	132	66.0	66	24	34	6.8
90	135	S107,5x3,6	131	65.5	66	24	45	8.2
110	158	S127,5x3,6	131	65.5	66	25	40	10.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>