



PROGEF Standard Übergangs-Nippel Metrisch R SDR11 (PN10)

Ausführung:

- Material: PP-H
- Mit Stumpfschweiss-Stutzen und konischem Aussengewinde
- Keine PP-schädigenden Gewindedichtpasten verwenden
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden

d	Gewindetyp	Zoll	PN	SDR	SM	Code	SP	Gewicht	L	L1	s	e
(mm)		(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)
20	R	½	10	11	IR	727 910 556	10	0.013	51	23	32	1.9
25	R	¾	10	11	IR	727 910 557	10	0.014	52	23	36	2.3
32	R	1	10	11	IR	727 910 558	10	0.027	55	23	46	2.9
40	R	1 ¼	10	11	IR	727 910 559	10	0.041	58	23	55	3.7
50	R	1 ½	10	11	IR	727 910 560	10	0.062	60	23	65	4.6
63	R	2	10	11	IR	727 910 561	5	0.096	67	26	80	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>