



PROGEF Standard Übergangs-Muffe Metrisch Rp SDR11 (PN10)

Ausführung:

- Material: PP-H
- Mit Stumpfschweisstützen **SDR11** und zylindrischem Rohr-Innengewinde Rp, verstärkt
- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Keine PP-schädigenden Gewindedichtpasten verwenden
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden

d	Gewindetyp	Zoll	PN	SDR	SM	Code	SP	Gewicht	L	L1	s	e
(mm)		(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)
20	Rp	½	10	11	IR	727 910 266	10	0.017	49	23	32	1.9
25	Rp	¾	10	11	IR	727 910 267	10	0.022	50	23	36	2.3
32	Rp	1	10	11	IR	727 910 268	10	0.038	54	23	46	2.9
40	Rp	1 ¼	10	11	IR	727 910 269	10	0.066	56	23	55	3.7
50	Rp	1 ½	10	11	IR	727 910 270	10	0.090	60	23	65	4.6
63	Rp	2	10	11	IR	727 910 271	20	0.123	62	23	80	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>