




ecoFIT T 90° egal PE100
d20-500mm / SDR11

Ausführung:

- Konventionelle Stumpfschweissung nach DVS 2207
- IR = Infrarot (IR Plus) kompatibel. Zu verschweissen mit Parameter PE100



d	DN	PN	SDR	SM	Code	Gewicht	L	L1	e
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)
20	15	16	11	IR	753 208 606	0.013	38	17	1.9
25	20	16	11	IR	753 208 607	0.021	42	17	2.3
32	25	16	11	IR	753 208 608	0.042	46	17	2.9
40	32	16	11	IR	753 208 609	0.065	51	22	3.7
50	40	16	11	IR	753 208 610	0.111	58	22	4.6
63	50	16	11	IR	753 208 611	0.202	66	21	5.8
75	65	16	11	IR	753 208 612	0.312	75	20	6.8
90	80	16	11	IR	753 208 613	0.553	90	20	8.2
110	100	16	11	IR	753 208 614	1.002	110	20	10.0
125	100	16	11	IR	753 208 615	1.509	125	25	11.4
140	125	16	11	IR	753 208 616	2.105	140	28	12.7
160	150	16	11	IR	753 208 617	3.085	160	28	14.6
180	150	16	11	IR	753 208 618	5.740	214	94	16.4
200	200	16	11	IR	753 208 619	5.982	200	35	18.2
225	200	16	11	IR	753 208 620	8.090	220	35	20.5
250	250	16	11		753 208 621	10.770	225	68	22.7
280	250	16	11		753 208 622	15.950	265	87	25.4
315	300	16	11		753 208 623	21.285	285	88	28.6
355	350	16	11		753 208 624	32.600	345	105	32.3
400	400	16	11		753 208 625	42.900	365	105	36.4
450	450	16	11		753 208 626	63.300	425	135	40.9
500	500	16	11		753 208 627	86.000	470	155	45.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>