



Klebeverschraubung PVC-U metrisch Silikonfrei

Ausführung:

- Lackstörungsfrei gereinigt / silikonfrei
- Einlegteil: Klebemuffe metrisch
- Einschraubteil: Klebemuffe metrisch
- Dichtfläche: mit O-Ring

d	Zoll	PN	EPDM	SP	Gewicht	FKM	SP	Gewicht
(mm)	(inch)	(bar)	Code		(kg)	Code		(kg)
10		16	721 510 178	1	0.022	721 510 153	1	0.020
12		16	721 510 179	1	0.022	721 510 154	1	0.019
16		16	721 510 180	1	0.026	721 510 155	1	0.031
20		16	721 510 181	1	0.042	721 510 156	1	0.040
25		16	721 510 182	1	0.067	721 510 157	1	0.066
32		16	721 510 183	1	0.100	721 510 158	1	0.090
40		16	721 510 184	1	0.180	721 510 159	1	0.175
50		16	721 510 185	1	0.206	721 510 160	1	0.215
63		16	721 510 186	1	0.357	721 510 161	1	0.380
75	2 1/2	10	721 510 187	1	0.615	721 510 162	1	0.615
90		10	721 510 188	1	0.925	721 510 163	1	0.925
110		10	721 510 189	1	1.425	721 510 164	1	1.425

d	L2	z1	z2	D	L1	G/Tr
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(inch)
10	22	3	10	31	15	5 - 8
12	22	3	10	31	15	5 - 8
16	24	3	10	35	17	3 - 4
20	26	3	10	43	19	1
25	29	3	10	51	22	1 1/4
32	33	3	10	58	25	1 1/2
40	39	3	12	72	29	2
50	46	3	14	83	34	2 1/4
63	58	3	18	100	41	2 3/4
75	62	3	18	135	47	Tr108x5
90	69	5	18	158	56	Tr 128x5
110	72	5	11	188	66	TR154x6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>