



T 90° PVC-U metrisch Rp

Ausführung:

- Mit Klebemuffen metrisch, Abzweig mit zylindrischem Rohr-Innengewinde Rp
- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

d	Gewindetyp	Zoll	PN	Code	SP	Gewicht	z1	z2	D	D1	L
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
12	Rp	1/4	16	721 200 204	10	0.015	7	7	17	20	19
16	Rp	3/8	16	721 200 205	10	0.027	9	9	21	25	23
20	Rp	1/2	16	721 200 206	10	0.029	11	13	26	30	29
25	Rp	3/4	16	721 200 207	10	0.043	14	15	32	35	33
32	Rp	1	16	721 200 208	10	0.080	17	19	40	45	39
40	Rp	1 1/4	16	721 200 209	10	0.134	23	26	47	55	49
50	Rp	1 1/2	16	721 200 210	5	0.212	27	36	59	59	59
63	Rp	2	16	721 200 211	5	0.379	33	46	74	75	71

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>