



Übergangsmuffe PVC-U metrisch Rp Verstärkt

Ausführung:

- Mit Klebemuffe metrisch und zylindrischem Rohr-Innengewinde Rp
- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

d	Gewindetyp	Zoll	PN	Code	SP	Gewicht	z	L	s
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)
12	Rp	¼	16	721 910 204	10	0.010	4	27	22
16	Rp	⅜	16	721 910 205	10	0.016	5	31	27
20	Rp	½	16	721 910 206	10	0.025	5	36	32
25	Rp	⅝	16	721 910 207	10	0.032	5	40	36
32	Rp	1	16	721 910 208	10	0.057	5	45	46
40	Rp	1 ¼	16	721 910 209	10	0.087	5	51	55
50	Rp	1 ½	16	721 910 210	10	0.126	7	59	65
63	Rp	2	16	721 910 211	5	0.206	7	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>