



PRO-FIT Winkel 45° PVC-U metrisch

Ausführung:

- Abgang A = Klebemuffe metrisch
- Abgang B = Klebestutzen kombiniert mit reduzierter Klebemuffe metrisch
- Direkte Verbindung Fitting mit Fitting ermöglicht kürzeste Baulänge

d	d1	PN	Code	SP	Gewicht	z	z1	z2	D	L	L1
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	16	16	721 150 306	10	0.010	5	9	11	25	21	25
25	20	16	721 150 307	10	0.015	6	11	14	31	25	30
32	25	16	721 150 308	10	0.027	8	13	16	38	30	35
40	32	16	721 150 309	5	0.053	10	17	21	47	36	43
50	40	16	721 150 310	5	0.090	12	18	23	58	43	49
63	50	16	721 150 311	5	0.175	14	23	30	73	52	61

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>