




ELGEF Plus T 90° reduziert PE100
d63-d315mm / SDR11 / Langschenklige Version

Ausführung:

- Druckstufe: 16 bar Wasser / 5 bar Gas
- Die Fittings wurden im Spritzgussverfahren hergestellt
- * FM 1613 zugelassen – 15 bar



d	d1	SDR	PN	DN	Code	Gewicht	z	z1	L	L1	e	e1
(mm)	(mm)		(bar)	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	32	11	16	50	753 201 022	0.300	218	86	65	47	5.8	3.0
63	40	11	16	50	753 201 026	0.312	230	107	67	58	5.8	3.7
63	50	11	16	50	753 201 021	0.300	218	100	65	59	5.8	4.6
75	32	11	16	65	753 201 023	0.455	248	98	73	46	6.8	3.0
75	50	11	16	65	753 201 024	0.485	248	109	73	58	6.8	4.6
75	63	11	16	65	753 201 025	0.520	248	118	73	65	6.8	5.8
90	50	11	16	80	753 201 027	0.794	280	120	79	55	8.2	4.6
90	63	11	16	80	753 201 029	0.775	282	127	79	63	8.2	5.8
90	75	11	16	80	753 201 055	0.800	286	132	80	75	8.2	6.8
110	63	11	16	100	753 201 028	1.409	322	148	87	63	10.0	5.8
110	75	11	16	100	753 201 131	1.382	324	155	85	74	10.0	6.8
110	90	11	16	100	753 201 032	1.275	322	164	86	79	10.0	8.2
125	90	11	16	100	753 201 132	1.997	354	165	90	82	11.4	8.2
125	110	11	16	100	753 201 133	2.097	350	167	90	85	11.4	10
160	63	11	16	150	753 201 034	2.680	416	174	105	65	14.6	5.8
160	75	11	16	150	753 201 880	2.295	410	180	103	73	14.6	6.8
160	90	11	16	150	753 201 036	2.775	415	190	101	79	14.6	8.2
160	110	11	16	150	753 201 037	3.300	415	200	101	82	14.6	10.0
180	90	11	16	150	753 201 881	4.857	476	200	108	82	16.4	8.2
180	110	11	16	150	753 201 882	4.750	480	202	107	84	16.4	10.0
180	63	11	16	150	753 201 883	4.715	480	220	110	101	16.4	14.6
200	63	11	16	200	753 201 073	7.300	503	196	122	63	18.2	5.8
200	90	11	16	200	753 201 074	9.730	500	216	122	79	18.2	8.2
200	110	11	16	200	753 201 075	7.120	505	219	122	82	18.2	10.0
200	160	11	16	200	753 201 076	9.730	500	237	122	98	18.2	14.6
225	75	11	16	200	753 201 039	9.880	560	219	120	70	20.5	6.8
225	90	11	16	200	753 201 040	6.633	555	228	120	80	20.5	8.2
225	110	11	16	200	753 201 041	10.010	559	238	120	82	20.5	10.0
225	160	11	16	200	753 201 042	8.095	555	258	120	98	20.5	14.6
225	180	11	16	200	753 201 043	9.375	559	284	120	105	20.5	16.4
250	110	11	16	250	753 201 078	11.820	584	284	130	82	22.7	10.0
250	160	11	16	250	753 201 079	12.302	586	266	127	98	22.7	14.6
*	315	90	11	300	753 201 154	16.700	520	165	90	83	28.6	8.2
*	315	110	11	300	753 201 051	15.300	705	282	150	82	28.6	10.0
	315	160	11	300	753 201 052	22.998	705	301	150	102	28.6	14.6
	315	200	11	300	753 201 152	18.710	680	313	155	117	28.6	18.2
	315	225	11	300	753 201 153	20.160	680	320	153	125	28.6	20.5
	315	250	11	300	753 201 054	24.243	695	331	150	130	28.6	22.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com

