



Reduktionsnippel PVC-U metrisch Rp

Ausführung:

- Mit Klebestutzen metrisch und zylindrischem Rohr-Innengewinde Rp
- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

	d	Gewindetyp	Zoll	PN	Code	SP	Gewicht	z	D	L	s
	(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
*	12	Rp	1/4	16	721 910 404	10	0.008	3	20	27	22
	20	Rp	3/8	16	721 910 434	10	0.014	7	25	35	
	25	Rp	1/2	16	721 910 437	10	0.021	7	30	41	
	32	Rp	3/4	16	721 910 441	10	0.032	15	35	48	
	40	Rp	1	16	721 910 446	10	0.058	20	45	56	
	50	Rp	1 1/4	16	721 910 452	10	0.097	20	55	66	
	63	Rp	1 1/2	16	721 910 458	5	0.151	10	62	77	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>