



Type A




Type B




Type C




Type B



Type A



Type C



PROGEF Standard Vorschweissbund

Kombinierte Dichtfläche: flach und gerillt, S5/SDR11 (PN10)

Ausführung:

- Material: PP-H
- Konventionelle Stumpfschweissung nach DVS 2207
- IR = Infrarotschweißen kompatibel
- Passend für Flanschverbindungen metrisch (ab d110 auch für ANSI/ASME B 16.5)
- Bis d315, passend zu Absperrklappe Typ 567/578 und 038/039. Darüber PROGEF Standard Adapter für Absperrklappen SDR11 nutzen (d355-500)
- Dichtung: Profil-Flanschdichtung EPDM No. 48 44 07, FKM No. 49 44 07
- * Werkstoff: PP-R, nicht passend für Absperrklappen

d	SDR	DN	PN	SM	Code	SP	Gewicht
(mm)		(mm)	(bar)				(kg)
20	11	15	10	IR	727 798 706	10	0.015
25	11	20	10	IR	727 798 707	10	0.029
32	11	25	10	IR	727 798 708	10	0.042
40	11	32	10	IR	727 798 709	10	0.061
50	11	40	10	IR	727 798 710	20	0.091
63	11	50	10	IR	727 798 711	10	0.144
75	11	65	10	IR	727 798 712	1	0.243
90	11	80	10	IR	727 798 713	12	0.324
110	11	100	10	IR	727 798 714	1	0.441
125	11	100	10	IR	727 798 715	8	0.520
140	11	125	10	IR	727 798 716	10	0.800
160	11	150	10	IR	727 798 317	4	0.927
180	11	150	10	IR	727 798 318	3	1.026
200	11	200	10	IR	727 798 319	2	1.652
225	11	200	10	IR	727 798 320	2	1.665
250	11	250	10	IR	727 798 521	1	2.630
280	11	250	10	IR	727 798 322	1	2.521
315	11	300	10	IR	727 798 523	1	3.247
* 355	11	350	10		727 798 324	1	6.600
* 400	11	400	10		727 798 325	1	9.100
* 450	11	500	10		727 798 326	1	17.300
* 500	11	500	10		727 798 327	1	18.400

d	L	L1	L2	d1	d2	d3	d4	e	Typ	a°
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
20	50	29	7	26	45		16	1.9	A	
25	52	27	9	32	58		20	2.3	A	
32	54	28	10	40	68		26	2.9	A	
40	56	25	11	49	78		32	3.7	A	
50	62	32	12	60	88		40	4.6	A	
63	68	38	14	75	102		51	5.8	A	
75	80	43	16	89	122	66	61	6.9	B	30
90	80	41	17	105	138	78	73	8.2	B	30
110	80	40	18	125	158	100	90	10.0	B	30
125	82	35	25	132	158	114	102	11.4	B	25
140	89	39	25	155	188	127	114	12.8	B	27
160	92	40	25	175	212	151	127	14.6	C	30
180	92	40	30	180	212	154	148	17.4	B	30
200	100	35	32	232	268	203	174	19.3	C	30
225	100	35	32	235	268	210	196	21.7	C	30
250	120	45	36	285	320	252	203	24.0	C	
280	120	45	37	291	320	265	228	26.8	C	30
315	150	50	52	338	370	300	256	30.2	C	22
* 355	162	70	40	373	430	342	284	33.9	C	45
* 400	172	70	46	427	482	387	320	38.2	C	45
* 450	225	105	60	514	585	400	360	43.0	C	15
* 500	231	105	60	530	585	442	400	47.8	C	15

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>