



Übergangs-Muffennippel egal PVC-U metrisch R

Ausführung:

- Mit Klebemuffe metrisch und konischem Rohr-Aussengewinde R
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

d	Gewindetyp	Zoll	PN	Code	SP	Gewicht	z	L	s
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)
16	R	¾	16	721 910 705	10	0.011	20	34	27
20	R	½	16	721 910 706	10	0.018	24	40	32
25	R	¾	16	721 910 707	10	0.025	25	44	36
32	R	1	16	721 910 708	10	0.039	28	50	46
40	R	1 ¼	16	721 910 709	10	0.061	31	57	55
50	R	1 ½	16	721 910 710	10	0.092	32	63	65
63	R	2	16	721 910 711	5	0.161	38	76	80
75	R	2 ½	10	721 910 712	6	0.227	42	86	90
90	R	3	10	721 910 713	5	0.389	46	97	110
110	R	4	10	721 910 714	5	0.572	53	114	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>