



Übergangsmuffennippel PVC-U metrisch R

Ausführung:

- Mit Klebestutzen/Klebemuffe reduziert metrisch und konischem Rohr -Aussengewinde R
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

d (mm)	Gewindetyp	Zoll (inch)	PN (bar)	d1 (mm)	Code	SP	Gewicht (kg)	z (mm)	z1 (mm)	s (mm)
12	R	3/8	16	16	721 910 555	10	0.010	35	23	27
16	R	1/2	16	20	721 910 556	10	0.016	42	28	32
20	R	3/4	16	25	721 910 557	10	0.023	47	31	36
25	R	1	16	32	721 910 558	10	0.040	54	35	46
32	R	1 1/4	16	40	721 910 559	10	0.061	60	38	55
40	R	1 1/2	16	50	721 910 560	10	0.094	66	40	65
50	R	2	16	63	721 910 561	5	0.164	78	47	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>