



Behälteranschluss variabel PVC-U

Ausführung:

- Dichtung: Flachdichtung EPDM
- Gleitring: PP
- Ersatzteile auf Anfrage

d (mm)	Zoll (inch)	d1 (mm)	Code	SP	Gewicht (kg)
20	¾	25	161 050 206	75	0.046
25	1	32	161 050 207	50	0.066
32	1 ¼	40	161 050 208	50	0.106
40	1 ½	50	161 050 209	35	0.190
50	2	63	161 050 210	25	0.248
63	2 ½	75	161 050 211	15	0.352
75	3	90	161 050 212	20	0.539
90		110	161 050 213	10	1.083
110		125	161 050 214	6	1.350

d (mm)	L3 max (mm)	Bohrung in Behäl- terwand (mm)	G (inch)	L1 (mm)	L2 (mm)	L (mm)	L4 (mm)	s (mm)	M
20	23	28	¾	13	19	42	16	32	
25	23	35	1	15	22	45	19	40	
32	24	43	1 ¼	17	26	49	22	50	
40	21	55	1 ½	19	31	48	26	60	
50	21	61	2	21	38	52	31	69	
63	23	77	2 ½	23	44	53	38	85	
75	20	89	3	26	51	56	44	100	
90	20	115		32	61	62	51	125	M113
110	22	135		36	69	66	61	147	M133

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>