



T 90° egal PVC-U Rp

Ausführung:

- Mit zylindrischem Rohr-Innengewinde Rp
- Anschluss nur für Kunststoffgewinde
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

Rp	PN	Code	SP	Gewicht	z	D	L
(inch)	(bar)			(kg)	(mm)	(mm)	(mm)
3/8	10	721 201 605	10	0.016	9	23	23
1/2	10	721 201 606	10	0.027	12	28	27
3/4	10	721 201 607	10	0.039	15	33	33
1	10	721 201 608	5	0.072	19	41	39
1 1/4	10	721 201 609	100	0.146	27	50	49
1 1/2	10	721 201 610	10	0.267	36	62	60
2	10	721 201 611	10	0.485	44	77	72

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>