





PROGEF Standard T 90° reduziert SDR11/PN10

Ausführung:


- Material: PP-H
- Konventionelle Stumpfschweißung nach DVS 2207
- IR = Infrarotschweißen kompatibel

¹mit IR geschweisster Reduktion




d (mm)	d1 (mm)	SDR	PN (bar)	SM	Code	NPK	Gewicht (kg)
63	32	11	10	IR	727 208 351		0.161
63	40	11	10	IR	727 208 350		0.165
63	50	11	10	IR	727 208 352		0.170
75	32	11	10	IR	727 208 353		0.238
75	50	11	10	IR	727 208 354		0.249
75	63	11	10	IR	727 208 355		0.258
90	50	11	10	IR	727 208 357		0.420
90	63	11	10	IR	727 208 358		0.428
90	75	11	10	IR	727 208 359		0.430
110	32	11	10	IR	727 208 360		0.652
110	50	11	10	IR	727 208 361		0.659
110	63	11	10	IR	727 208 362		0.665
110	75	11	10	IR	727 208 363		0.681
110	90	11	10	IR	727 208 364		0.701
1	125	63	11	IR	727 208 365		1.680
1	125	90	11	IR	727 208 066		1.700
1	125	110	11	IR	727 208 367		1.700
1	140	75	11	IR	727 208 068		2.400
1	140	90	11	IR	727 208 069		2.358
	160	63	11	IR	727 208 371		2.130
	160	75	11	IR	727 208 372		2.143
	160	90	11	IR	727 208 373		2.148
1	140	110	11	IR	727 208 370		2.380
	160	110	11	IR	727 208 374		2.186
	160	125	11	IR	727 208 075		3.600
1	200	160	11	IR	727 208 385		6.632
	200	180	11	IR	727 208 086		6.900
	225	90	11	IR	727 208 388		4.576
	225	110	11	IR	727 208 389		4.624
	225	160	11	IR	727 208 391		4.685
	250	160	11		727 208 093		12.500

L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	e (mm)	e1 (mm)
65	70	25	25	5.8	2.9
65	70	25	25	5.8	3.7
65	70	25	25	5.8	4.6
70	75	25	25	6.8	2.9
70	75	25	25	6.8	4.6
70	75	25	25	6.8	5.8
80	85	25	25	8.2	4.6
80	85	25	25	8.2	5.8
80	85	25	25	8.2	6.8
90	95	30	25	10.0	2.9
90	95	30	25	10.0	4.6
90	95	30	25	10.0	5.8
90	95	30	25	10.0	6.8
90	95	30	25	10.0	8.2
1	125	230	25	11.4	5.8
1	125	225	25	40	8.2



1



	L	L1	L2	L3	e	e1
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
1	125	217	25	30	11.4	10.0
1	140	245	28	41	12.7	6.8
1	140	240	28	40	12.7	8.2
	142	135	50	30	14.6	5.8
	142	135	50	30	14.6	6.8
	142	135	50	30	14.6	8.2
1	140	242	28	33	12.7	10.0
	142	135	50	30	14.6	10.0
	160	272	28	32	14.6	11.4
1	200	332	35	40	18.2	14.6
	200	335	35	45	18.2	16.4
	155	165	40	30	20.5	8.2
	155	165	40	30	20.5	10.0
	155	165	40	30	20.5	14.6
	227	387	68	53	22.7	14.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>