



ecoFIT Reduktions-Nippel metrisch PE100 d20-50mm / SDR11 / Innengewinde Rp

Ausführung:

- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Keine PE-schädigenden Gewindedichtpasten verwenden
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Mit Schweissstutzen metrisch und zylindrischem Rohr-Innengewinde Rp, verstärkt

d	Gewindetyp	Zoll	DN	PN	SDR	Code	Gewicht	L	z
(mm)		(inch)	(mm)	(bar)			(kg)	(mm)	(mm)
20	Rp	¾	15	10	11	733 910 434	0.012	33	7
25	Rp	½	20	10	11	733 910 437	0.015	37	6
32	Rp	¾	25	10	11	733 910 441	0.028	43	8
40	Rp	1	32	10	11	733 910 446	0.046	49	9
50	Rp	1 ¼	40	10	11	733 910 452	0.071	55	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>