



Doppelnippel PVC-U R

Ausführung:

- Mit konischem Rohr-Aussengewinde R
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

Gewindetyp	Zoll (inch)	PN (bar)	Typ	Code	SP	Gewicht (kg)	L (mm)	s (mm)
R	3/8	10	A	721 911 905	10	0.007	37	19
R	1/2	10	A	721 911 906	10	0.012	45	22
R	3/4	10	A	721 911 907	10	0.019	49	27
R	1	10	A	721 911 908	10	0.034	57	36
R	1 1/4	10	A	721 911 909	10	0.052	62	46
R	1 1/2	10	A	721 911 910	10	0.070	67	50
R	2	10	A	721 911 911	10	0.126	76	65

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>