



ecoFIT Verschraubung PE100 / SDR17 / d75-110mm

Ausführung:

- Konventionelle Stumpfschweißung nach DVS 2207
- IR = (IR Plus®) kompatibel
- O-Ring Dichtung EPDM/FKM
- ecoFIT Überwurfmutter Material: PP Glasfaserverstärkt
- Für die Dimensionen d75--110 bitte die Hinweise für die Montage beachten

d (mm)	DN (mm)	PN (bar)	SDR	SM	EPDM Code	FKM Code	Gewicht (kg)
75	65	10	17	IR	753 518 412	753 528 412	0.476
90	80	10	17	IR	753 518 413	753 528 413	0.483
110	100	10	17	IR	753 518 414	753 528 414	0.663

d	D	G	L	L1	L2	e
(mm)	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)
75	135	S107,5x3,6	132	66	66	4.3
90	135	S107,5x3,6	131	66	66	5.1
110	158	S127,5x3,6	131	66	66	6.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>