



ecoFIT Reduktion PE100 S5/SDR11

Ausführung:

- Konventionelle Stumpfschweissung nach DVS 2207

d	d1	Code	SP	Gewicht	L	L1	L2	e	e1
(mm)	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
75	32	700 645 618	0	0.056	70	30	25	6.9	3,0
90	50	700 645 619	0	0.094	80	35	28	8.2	4,6
110	50	700 645 620	0	0.161	90	35	34	10.0	4,6
110	63	700 645 621	0	0.165	90	35	35	10.0	5,8
125	63	700 645 622	0	0.186	100	40	38	11.4	5,8
125	75	700 645 623	0	0.207	100	40	38	11.4	6,9
125	90	700 645 624	0	0.211	100	40	43	11.4	8,2
140	75	700 645 625	0	0.255	110	50	37	12.8	6,9
140	90	700 645 626	0	0.272	110	50	39	12.8	8,2
160	90	700 645 627	0	0.420	120	55	40	14.6	8,2
160	125	700 645 628	0	0.369	120	55	48	14.6	11,4
200	140	700 645 634	0	0.754	140	60	48	18.2	12,8
225	140	700 645 636	0	1.030	160	65	55	20.5	12,8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>