



ecoFIT Rückschlagventil Typ 561 PVC-U

Ohne Feder

Mit Stumpfschweisssutzen lang PE100 SDR11 metrisch

Ausführung:

- Werkstoff: PVC-U/PE
- Leicht ein- und ausbaubar
- Vibrationsfrei auch bei hohen Durchflussgeschwindigkeiten
- Strömungsoptimierter Rückschlagkegel, zweifach geführt
- Vertikaler Einbau
- Gleiche Einbaumasse wie Kugelhahn Typ 546
- Z-Mass, Anschlussstiel und Überwurfmutter sind **nicht kompatibel** zu Typ 360

d (mm)	DN (mm)	Zoll (inch)	PN (bar)	kv-Wert ($\Delta p=1$ bar) (L/min)	SDR	EPDM Code	NPK	Gewicht (kg)
20	15	½	16	180	11	161 561 142	582 112	0.130
25	20	¾	16	380	11	161 561 143	582 113	0.260
32	25	1	16	460	11	161 561 144	582 114	0.300
40	32	1 ¼	16	850	11	161 561 145	582 115	0.520
50	40	1 ½	16	1080	11	161 561 146	582 116	0.780
63	50	2	16	1670	11	161 561 147	582 117	1.410
75	65	2 ½	10	2950	11	161 561 148		3.260
90	80	3	10	3600	11	161 561 149		5.170
110	100	4	10	4150	11	161 561 150		8.310

d (mm)	FKM Code	NPK	Gewicht (kg)	D (mm)	L (mm)	L2 (mm)	e (mm)	closest inch (inch)
20	800 050 344		0.130	50	193	56	2.3	½
25	800 050 345		0.250	58	216	65	2.3	¾
32	800 050 346		0.320	68	223	71	3.0	1
40	800 050 308		0.530	84	249	85	3.7	1 ¼
50	800 050 347		0.810	97	271	89	4.6	1 ½
63	800 050 348		1.530	124	321	101	5.8	2
75	800 050 837		3.160	166	386	136		2 ½
90	800 048 959		5.520	200	421	141	8.2	3
110	800 050 839		8.930	238	484	164	10.0	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>