



PROGEF Standard Verschraubung (PN10)

Ausführung:

- Material: PP-H
- Schweissmuffe metrisch
- d75-110 mit neuer Gewindegeometrie und Nenndruck PN10 bis d110
- Dichtfläche mit O-Ring Nut
- **Für die Dimensionen d75-110 bitte die Hinweise für die Montage beachten.**

d (mm)	PN (bar)	EPDM Code	NPK	FKM Code	NPK	Gewicht (kg)
16	10	727 510 155	435 111	727 520 155		0.020
20	10	727 510 156	435 112	727 520 156		0.038
25	10	727 510 157	435 113	727 520 157		0.062
32	10	727 510 158	435 114	727 520 158		0.080
40	10	727 510 159	435 115	727 520 159		0.137
50	10	727 510 160	435 116	727 520 160		0.136
63	10	727 510 161	435 117	727 520 161		0.251
75	10	727 510 192		727 520 192		0.427
90	10	727 510 193		727 520 193		0.625
110	10	727 510 194		727 520 194		1.161

d (mm)	L1 (mm)	L2 (mm)	D (mm)	G (inch)	z1 (mm)	z2 (mm)
16	18	24	35	3/4	3	9
20	19	26	48	1	3	10
25	21	28	58	1 1/4	3	10
32	23	30	65	1 1/2	3	10
40	25	34	79	2	3	12
50	28	39	91	2 1/4	3	14
63	32	47	111	2 3/4	3	18
75	36	51	138	S110x5	3	18
90	42	55	161	S130x5	5	18
110	49	54	191	S155x5	6	12

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>