



PROGEF Standard Reduktions-Nippel Metrisch Rp (PN10)

Ausführung:

- Material: PP-H
- Mit Schweissstutzen metrisch und zylindrischem Rohr-Innengewinde Rp, verstärkt
- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Keine PP-schädigenden Gewindedichtpasten verwenden
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden

d	Gewindetyp	Zoll	PN	Code	SP	Gewicht	L	z
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)
20	Rp	¾	10	727 910 433	10	0.011	36	7
20	Rp	¾	10	727 910 434	10	0.011	36	7
25	Rp	½	10	727 910 437	10	0.015	45	6
32	Rp	¾	10	727 910 441	10	0.022	47	8
40	Rp	1	10	727 910 446	10	0.039	53	9
50	Rp	1 ¼	10	727 910 452	10	0.061	55	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>