




**PROGEF Standard T 90° egal
SDR11/PN10**

Ausführung:

- Material: PP-H
- Konventionelle Stumpfschweissung nach DVS 2207
- IR = Infrarotschweissen kompatibel

¹ Material: PP-R



d	SDR	PN	SM	Code	NPK	Gewicht	L	L1	e
(mm)		(bar)				(kg)	(mm)	(mm)	(mm)
20	11	10	IR	727 208 506		0.011	38	21	1.9
25	11	10	IR	727 208 507		0.018	42	21	2.3
32	11	10	IR	727 208 508		0.032	46	21	2.9
40	11	10	IR	727 208 509	432 165	0.062	51	23	3.7
50	11	10	IR	727 208 510		0.105	58	22	4.6
63	11	10	IR	727 208 511		0.186	66	20	5.8
75	11	10	IR	727 208 512		0.293	75	20	6.8
90	11	10	IR	727 208 513		0.521	90	20	8.2
110	11	10	IR	727 208 514		0.928	110	20	10.0
125	11	10	IR	727 208 515		1.347	125	25	11.4
140	11	10	IR	727 208 516		1.923	140	28	12.7
160	11	10	IR	727 208 517		2.844	160	28	14.6
180	11	10	IR	727 208 518		5.475	215	94	16.4
200	11	10	IR	727 208 519		5.579	200	35	18.2
225	11	10	IR	727 208 520		7.812	220	35	20.5
250	11	10	IR	727 208 521		10.400	227	68	22.7
280	11	10	IR	727 208 522		15.170	267	87	25.4
315	11	10	IR	727 208 523		20.330	283	86	28.6
1	355	11	10	--	727 208 524	31.100	345	105	32.2
1	400	11	10	--	727 208 525	40.900	365	105	36.3
1	450	11	10	--	727 208 526	60.300	425	135	40.9
1	500	11	10	--	727 208 527	81.900	470	155	45.4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>