



PROGEF Standard Verschraubung SDR11 (PN10)

Ausführung:

- Material: PP-H
- IR = Infrarotschweissen kompatibel
- Konventionelle Stumpfschweissung nach DVS 2207

Mit Stumpfschweiss-Stutzen

Dichtung: O-Ring EPDM

Für die Dimensionen d75-110 bitte die Hinweise für die Montage beachten.

d (mm)	SDR	PN (bar)	SM	EPDM Code	NPK	FKM Code	NPK	Gewicht (kg)
20	11	10	IR	727 518 506		727 528 506		0.047
25	11	10	IR	727 518 507		727 528 507		0.072
32	11	10	IR	727 518 508		727 528 508		0.100
40	11	10	IR	727 518 509		727 528 509		0.145
50	11	10	IR	727 518 510		727 528 510		0.190
63	11	10	IR	727 518 511		727 528 511		0.332
75	11	10	IR	727 518 212		727 528 212		0.520
90	11	10	IR	727 518 213		727 528 213		0.533
110	11	10	IR	727 518 214		727 528 214		0.754

d (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	D (mm)	G (inch)	e (mm)
20	107.0	54.0	53.0	26	37	48	1	1.9
25	113.0	57.0	56.0	26	36	58	1 1/4	2.3
32	119.0	60.0	59.0	26	25	65	1 1/2	2.9
40	126.0	63.0	63.0	26	25	79	2	3.7
50	131.0	65.5	65.5	26	25	91	2 1/4	4.6
63	137.0	69.0	68.0	26	26	111	2 3/4	5.8
75	134.5	68.5	66.0	26	34	138	S110x5	6.8
90	134.5	68.5	66.0	26	45	138	S110x5	8.2
110	139.5	74.0	65.5	33	40	161	S130x5	10.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>